RAILING SYSTEMS
Balustrade S25 Link Rail

Product	Model	Sizes mm	Finish	Material	Type	Application	Area
S25 LINK RAIL	300738	5800mm	SS	2205 STAINLESS STEEL	LINK RAIL	BALUSTRADE LINK RAIL	Internal & External
		GLASS THICKNESS: 10–12mm OVERALL SIZE: 25 x 21mm	ON REQUEST: POWDERCOAT				
S25 LINK RAIL WALL BRACKET (LEFT HAND)	300118	Suits S25 Rail	SS	2205 STAINLESS STEEL	WALL BRACKET	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 LINK RAIL WALL BRACKET (RIGHT HAND)	301854	Suits S25 Rail	SS	2205 STAINLESS STEEL	WALL BRACKET	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 LINK RAIL VERTICAL ADJUSTABLE	300863	Suits S25 Rail	SS	2205 STAINLESS STEEL	ADJUSTABLE JOINER	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 LINK RAIL HORIZONTAL ADJUSTABLE	300862	Suits S25 Rail	SS	2205 STAINLESS STEEL	ADJUSTABLE HORIZONTAL JOINER	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 LINK RAIL FIXED 90 DEGREE CORNER	300861	Suits S25 Rail	SS	2205 STAINLESS STEEL	90 DEGREE CORNER CONNECTOR	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 LINK RAIL INLINE JOINER	300864	Suits S25 Rail	SS	2205 STAINLESS STEEL	INLINE JOINER	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
S25 END CAP	300512	Suits S25 Rail	SS	2205 STAINLESS STEEL	END CAP	BALUSTRADE LINK RAIL COMPONENT	Internal & External
			ON REQUEST: POWDERCOAT				
LINK RAIL LOCTITE 243	300961	Suits S25 Rail	ADHESIVE	50ML BOTTLE	TUBE LOCK ADHESIVE	BALUSTRADE LINK RAIL COMPONENT	Internal & External
S25 LINK RAIL RUBBER GASKET	302091	Suits S25 Rail	BLACK	RUBBER	RUBBER GASKET FOR S25 LINK RAIL	BALUSTRADE LINK RAIL COMPONENT	Internal & External
		PER METRE LENGTH GLASS THICKNESS: 12mm					
GRUB SCREW	301978	M5x6mm	SS	316 STAINLESS STEEL	GRUB SCREW	BALUSTRADE LINK RAIL FIXING	Internal & External

Link Rail System
S25 Link Rail

▶ 25 x 21mm 2205 Stainless Steel.
▶ Suitable for 10mm to 12mm glass thicknesses.
▶ Rail Components available for 90 degree corners, adjustable corners (180 degrees to 90 degrees), stairway link connectors (Maximum 35 degrees), inline joiner.
▶ Wall mount brackets available including end caps.
▶ Satin stainless steel finish standard, powder-coating available by request.

Compliance
▶ Complies with NZS 4223.3.2016 and the latest amendment of New Zealand Building Code B1.
▶ Maximum width of glass panel is 1900mm when S25 used as a glass mounted interlinking rail.